

# SELF PROPELLED FERTILIZER APPLICATOR

## SR-18c

## MORE USABILITY

### CHARACTERISTICS

1. TEA FIELD, ORCHARD, APPLICABLE TO VARIETY OF FIELDS
2. CHOOSABLE APPLICATION SIDED (LEFT, RIGHT, BOTH)
3. CORE COMPONENTS ARE MADE FROM STAINLESS STEEL  
RUST RESISTANT
4. LIGHTER GRIP ON CLUTCH LEVER



DIAL SYSTEM ENABLES



EASY PULL CLUTCH LEVER  
AND SMOOTH OPERATING  
SHUTTERS



GRANULAR AND BLENDED FERTIZIER ARE

SPECIFICATION		
SIZE	LENGTH (mm)	1100
	WIDTH (mm)	560
	HEIGHT (mm)	1000
	WEIGHT (kg)	67.5
BUCKET CAPACITY (L)		60
MAXIMUM APPLICATION WIDTH (mm)		1500
SPEED	FORWARD1 (km/h)	3.0
	FORWARD2 (km/h)	4.1
ENGINE	MODEL	MITSUBISHI
	TYPE	AIR COOLING 4CYCLE
	DISPLACEMENT (cc)	98
	MAXIMUM OUTPUT (kW [PS])	2.2 (3.0)
	FUEL	UNLEADED PETROL
	FUEL CAPACITY (L)	1.6
AIR CLEANER		OIL BATH

※MACHINE SPECIFICATION MAY CHANGE WITH OR WITHOUT NOTICE FOR IMPROVEMENT.

※SOME FERTILISER (SIZE AND/OR MOISTURE CONTENT) MAY HARD TO APPLY WITH

